



Scan QR code for more info

customers the most accurate details in order for them to make an informed decision on our range. However, there may occasionally be errors or omissions and we reserve the right to amend or remove specifications without notice.

This document was produced in **May 2019** and the reliability and accuracy of this data should be checked by the reader prior to design or purchase.



gclproducts.co.uk



sales@gclproducts.co.uk



+44 (0)1246 418144

X-Grid Anchor Pegs

Strong and Robust Anti-Pull Fixing Solution

The ribbed, anti-pull design of our anchor pegs prevents the fixings from being pulled out of the ground. They ensure that all X-Grid panels and other products remain in place under even the most testing of conditions. Manufacture from a durable plastic polymer, these anti-pull pegs are also weatherproof and UV resistant which ensures each peg has a long serviceable life and will not rot away or break down over time. Available in packs of 1, 5, 25, 50 and 100, you can order the precise amount of pegs for your upcoming project which requires a strong, versatile, safe and easy to use fixing. Designed with a sharp point, each peg can effectively penetrate a range of fabrics and surfaces.



KEY FACTS

Length: 200mm

Width: 70mm

Diameter: 25mm

Weight: 0.28kg

Pack sizes: **Single, 5, 25, 50** & 100

Colour: Black

Material: Co-polymer Polypropylene

Pegs used per sqm: 5 pegs

» Anti-pull ribs: Yes

APPLICATIONS



X-GRID

Used mainly with X-Grid when installed on an incline to prevent movement



MEMBRANES

Can be used on almost all membrane installs where a strong fixing is needed



GRASSMESH

Secures and holds GrassMesh in place that will experience machinery traffic



TURFMESH

Fixes & holds TurfMesh in place when vehicles will be driving over the mesh



SHED BASE

Holds plastic shed bases in place before the garden building is installed




HOT TUB BASE

Secures hot tub bases in place before & after the hot tub has been installed

Installation Instructions

- 1. Follow the installation guide of the product or products you are wanting to install for your project up until the point of using your X-Grid anchor pegs. You can continue following that installation guide once your pegs are in place and secure.
- 2. With your X-Grid panels, membrane or meshes in place you can begin using your anti-pull anchor pegs.
- **3.** We recommend using 5 pegs per sqm so ensure you evenly spread the anchors around. More can be used dependent on the intended use.
- **4.** Using a rubber mallet, hammer the peg through a gap in the X-Grid and mesh or pierce the membrane sheet. Hammer the peg down until it is sitting flush with the product.
- **5.** Repeat this process over and over until you have secured the entire area and that you are satisfied your grid, mesh or membrane will not migrate.
- **6.** Continue with the rest of your chosen products installation.





PRODUCT CODE	COLOUR	DESCRIPTION	DIA. (mm)	LENGTH & WIDTH (mm)	PACK SIZE	PALLET QTY	UNIT WEIGHT (kg)
XGAP200B	Black	Single X-Grid Anchor Peg	25	200mm x 70mm	1	-	0.28
XGAP200B-005	Black	5pk X-Grid Anchor Peg	25	200mm x 70mm	5	-	1.44
XGAP200B025	Black	25pk X-Grid Anchor Peg	25	200mm x 70mm	25	-	7.2
XGAP200B050	Black	50pk X-Grid Anchor Peg	25	200mm x 70mm	50	-	14.4
XGAP200B100	Black	100pk X-Grid Anchor Peg	25	200mm x 70mm	100	-	28.8