



Resin Bound Gravel

Attractive, strong and SuDs compliant surfacing

Resin bound gravel surfacing has seen a sharp increase in popularity over the past few years and shows no signs of slowing. It is an incredibly sought after surfacing solution thanks to its wide range of benefits which includes being **strong, attractive, durable, low maintenance, SuDs compliant, UV stable** and **long lasting**. Resin bound can be installed onto a range of sub-bases from recycled plastic ground reinforcement grids to permeable concretes. Created by mixing together bags of washed and kiln-dried decorative aggregates with a specially formulated resin binder in a forced action mixer creates a tacky material which is then installed by trained installers using trowels. The benefits of resin bound make it the ideal material for creating driveways, car parks, forecourts pathways, patios, terraces, urban areas and more

- RUBBER GRASS MATS
- RUBBER PLAY TILES
- BELT CONVEYORS
- STEEL FIXING PINS
- PLASTIC FIXING PEGS
- LAWN & BORDER EDGING
- FORCED ACTION MIXERS
- WATER STORAGE CRATES
- RESIN BOUND GRAVEL
- RUBBER GYM MATTING
- GRASS PROTECTION MESHES
- GRASS REINFORCEMENT MESHES
- GROUND REINFORCEMENT & GRAVEL RETENTION GRID
- SUBMERSIBLE COMBI PUMPS
- RECYCLED PLASTIC DECKING
- RECYCLED PLASTIC LUMBER
- LANDSCAPING & WEED CONTROL MEMBRANES



Scan QR code for more info

GCL Products Limited are dedicated to providing our customers the most accurate details in order for them to make an informed decision on our range. However, there may occasionally be errors or omissions and we reserve the right to amend or remove specifications without notice.

This document was produced in **March 2020** and the reliability and accuracy of this data should be checked by the reader prior to design or purchase.



gclproducts.co.uk



sales@gclproducts.co.uk



+44 (0)1246 418144

APPEARANCE
The unique gravel colours and kit blends make resin bound an attractive surfacing solution

SUDS COMPLIANT
Resin bound is a permeable surface which allows water to drain away naturally and help reduce surface water build up

STRONG
The specially formulated binder & gravel bind so well that resin bound is able to withstand cars & HGVs

VARIATION
We have over 40 different gravels and blends available to meet yours and your customers wants and needs

UV STABLE
If mixed with a UV stable resin, your resin bound surface will not fade away or alter when exposed to UV rays

LOW MAINTENANCE
This unique surface requires little to no maintenance. A simple brush or wash when required is all you need

VERSATILE
The benefits of resin bound gravel mean that it can be used as a surfacing solution for a number of applications

KEY FACTS

- » Gravels Available: **Over 40 Variants**
- » Gravel Bag Size: **25kg**
- » Types Of Binder: **UV Stable & Non-UV Stable**
- » Resin Binder Includes: **2 Components**
- » Resin Binder Bucket Size: **6.5kg**
- » A Standard Resin Bound Mix: **4 Gravel Bags and 1 Resin Binder**
- » Typical Installation Depths: **15mm for paths or walkways & 18mm for driveways and traffic areas**

APPLICATIONS

- DRIVEWAYS & CAR PARKS**
Replace traditional surfaces with a strong & attractive resin bound drive
- PATIOS & PATHS**
Resin bound gravel is ideal for creating appealing & long lasting patios & paths
- FORECOURTS**
Used to create strong and attractive areas front of car garages & sale rooms
- URBAN AREAS**
Used to create a variety of beautiful, permeable & durable urban areas
- TERRACES**
Create attractive terrace flooring which requires little to no maintenance
- RACECOURSES**
A popular surfacing solution for grandstand areas & parade rings

PRODUCT CODE	DESCRIPTION	PSV RATING	GRAVEL SIZE (mm)	PACK SIZE	UNIT WEIGHT (kg)
PPNUV	UV Stable Resin Binder	N/A	N/A	1	6.5kg
PPUVR	Non-UV Stable Resin Binder	N/A	N/A	1	6.5kg
GAG1-4/25	Amber Gold	35 - 40	1-4mm	1	25kg
AWG1-3/25	Arctic White	N/A	1-3mm	1	25kg
AWG2-5/25	Arctic White	N/A	2-5mm	1	25kg
AGG2-5/25	Autumn Gold	N/A	2-5mm	1	25kg
AQG1-3/25	Autumn Quartz	54	1-3mm	1	25kg
GAQ2-5/25	Autumn Quartz	54	2-5mm	1	25kg
GB2-5/25	Beige	N/A	2-5mm	1	25kg
GB1-3/25	Black	58	1-3mm	1	25kg
1495	Black	58	2-5mm	1	25kg
GGP1-3/25	Brittany Bronze	35 - 40	1-3mm	1	25kg
GGP2-5/25	Brittany Bronze	35 - 40	2-5mm	1	25kg
DRPB04	Brittany Bronze	35 - 40	10mm	1	25kg
CP1-3/25	Celtic Plum	68	1-3mm	1	25kg
CBAUX	Chinese Bauxite	70	1-3mm	1	25kg
GC1-3/25	Classic	52	1-3mm	1	25kg
GC2-5/25	Classic	52	2-5mm	1	25kg
2342	Copper Slag	N/A	1-3mm	1	25kg
DDY2-5/25	Devon Yellow	N/A	2-5mm	1	25kg
DRPD110	Dobbsweir	30 - 40	3-6mm	1	25kg
DMG1-2/12.5	Dolomite	48	1-2mm	1	25kg
GDG2-5/25	Dorset	35 - 40	2-5mm	1	25kg
DRPG31	Golden Pea	35 - 40	1-3mm	1	25kg
DRPG15	Golden Pea	35 - 40	2-5mm	1	25kg
GGQ2-5/25	Golden Quartz	35 - 40	2-5mm	1	25kg
GG2-5/25	Green	63	2-5mm	1	25kg
2343	Green Granite	63	1mm	1	25kg
GG2/25	Green Granite	63	2mm	1	25kg
2344	Green Granite	63	3mm	1	25kg
PQG1-3/25	Pearl Quartz	N/A	1-3mm	1	25kg
PQG2-5/25	Pearl Quartz	N/A	2-5mm	1	25kg
DRPP90	Pearl Quartz	N/A	5-8mm	1	25kg
GR1-3/25	Red	53	1-3mm	1	25kg
GR2-5/25	Red	53	2-5mm	1	25kg
DRPR64	Rhine Gold	N/A	10mm	1	25kg
GSP2-5/25	Salmon Pink	48	2-5mm	1	25kg
DRPS70	Silver	52	0-1mm	1	25kg
GS1-3/25	Silver	52	1-3mm	1	25kg
GS2-5/25	Silver	52	2-5mm	1	25kg
GS10/25	Silver	52	10mm	1	25kg
GSTP1-3/25	Staffs Pink	48	1-3mm	1	25kg
GSTP2-5/25	Staffs Pink	48 - 50	2-5mm	1	25kg
DRPR68	Trent Pea	35 - 40	3-6mm	1	25kg
DRPT104	TruGrip	68	1-3mm	1	25kg
WFG2-5/25	White Flint	57	2-5mm	1	25kg
DRPY78	Yellow	N/A	10mm	1	25kg
CG/25	Anti-Slip Crushed Glass	N/A	N/A	1	25kg
CHS52	Chelford 52 Sand	N/A	N/A	1	6.5kg