

# Technical data sheet

## BOUNDCLEAN — SURFACE CLEANER

Page: 1/1

Version V1 03.04.24

Date of print 14.02.2025

Type	All surface cleaner
Form Supplied	Clear Liquid
Uses	Efficient cleaner for all hard surfaces

### Specification

Colour	Clear
Odour	Odourless/ Slight detergent
Melting point	Less than 0°C
Boiling Point	Greater than 100°C
Flash Point	Not applicable
Miscibility in water	Soluble
pH (20°C)	Approximately 12.8

### Uses

Spray onto the surface to be cleaned, allow the dirt to dissolve for about 20 minutes before jet washing or rinse away with hot or cold water. The product should be used on dry surfaces with no rain forecast for at least 8 hours.

Reapply the product and leave for longer lasting protection from regrowth.

### Applications

Recommended for cleaning all types of dirt, gets rid of mould and algae and prevents regrowth. Can be used on patios, driveways, stone carpet, bare metals, painted surfaces, glass, vinyl, terrazzo, quarry tiles and concrete.

Always check for compatibility on surfaces on a small area before use.

If application of a sealer or a primer is desired after the cleaning process, allow the surface to be completely dry prior to use.

### Safety Information

The BOUNDCLEAN — Surface Cleaner is odourless, non-toxic and non-flammable, but users are encouraged to refer to the Material Safety Data Sheet corresponding to this product.

Keep out of reach of children.

**Note:** Any and all information or suggestions/recommendations provided by PERMABOUND Ltd. regarding the application of products supplied by the company, be this in the form of technical literature, or in correspondence relating to specific queries or otherwise, is based on data believed to be reliable. However, it is for the customer to decide for itself, the suitability of the product for their own particular use, based on their requisite skills and know-how within the industry, and it is therefore deemed by the company that the customer will have done so at their sole discretion and risk. No liability will be accepted by PERMABOUND Ltd should materials or methods prove to be unsuitable for any application.